



FILL-LITE™

The soft light company

www.fill-lite.com



Fill-Lite Studio

The largest thin profile soft light on the market, the Fill-Lite Studio is moveable north light window.

The Fill-Lite Studio comes out of a flight case in two pieces and mounts to a junior light stand, making one large amazing soft light. The controller includes manual dimming and daisy chaining to link fixtures, universal AC power input, and ports for optional battery and DMX 512 for studio use (wired or wireless).

The ultra thin profile mimics natural ambient light and eliminates the need for large softboxes. This fixture is the perfect solution for large soft light requirements, such as product, people and tabletop photography in tight spaces.

FEATURES

- Clean design
- Wrap around soft light
- Amazingly thin profile when mounted
- All-in-one fixture. No setup, just plug it in!
- Divides for easy packing
- Very low power requirement
- No heat from fixture. Excellent on talent, tabletop, or tight sets
- Controller contains all electronics, connects via twist-lock head cable

ACCESSORIES

- Soft egg crate 30° / 40° / 50° (SnapGrid™ SFF0404)
- Custom flight case
- DMX512 module plugin, field installed
- DMX over WiFi module plugin, field installed
- 24-36VDC Battery Inverter module plugin, field installed

SPECIFICATIONS

OPTICS

	DAYLIGHT	TUNGSTEN
CRI	90	93
TLCI	85	87
lux @1m	3715	

Beam Angle: 114°

LED Life: 50,000 hours

MECHANICAL DESIGN

- Description: Yoke mounted ultra-soft 51" (129.5cm) light square with custom designed solid state electronics
- Yoke uses a combination of powder coated and anodized steel and aluminum
- Onboard manual dimmer 0-100%
- 3.5mm link cable connection
- Heat sync /thermal
- Convection cooling, silent and cool to the touch
- Minimum/Maximum ambient operating temp: -0C to +40C

DIMENSIONS

- Panel only: 48"w x 48"h x 0.5"d (122cm x 122cm x 1.27cm)
(4 light squares permanently mounted together)
- Panel w/Yoke: 59"w x 54"h x 2.5"d (149.9cm x 137.2cm x 6.4cm)

WEIGHT

- Panel w/Yoke: 122lbs (55.3kg)

POWER

Input AC power: Universal 90-250 VAC

- Power consumption: 300 watt
 - Fused protection
- Input DC Power: 24-36 VDC @2-3A
- Connection: 3-pin XLR
(pin # 1 - / pin #2 + / pin #3 NC)

CERTIFICATIONS

- RoHs compliant
- UL/CE pending

WARRANTY

- 1 year parts and labor

PACKAGE INCLUDES

- Gel clips, mounted
- Baby female receiver
- Yoke with built-in power supply
- Safety pins w/bails to secure top to bottom panel
- Detachable US power cord (3-prong)